

MODULAR HOUSE TOY

5 Background of the Invention:

Field of the Invention:

The invention relates to toy houses, and more particularly, to a modular toy house.

10 Different toy houses have been made in the past. Most of the existing modular-like toy houses, however, exist as multi-piece construction sets. See, for example, U.S. Patent No. 1,898, 297 to Fox, U.S. Patent No. 3,020,601 to Stambaugh et al., U.S. Patent No. 3,571,965 to Gibb, U.S. Patent No. 4,270,302 to Dandia, U.S. Patent No. 4,306,372 to Lin, and U.S. Patent No. 4,487,690 to Stoffle et al.

15 One such multi-piece construction set is disclosed in U.S. Patent No. 5,876,261 to Bach et al., which discloses a self-supporting grating structure that, when fully assembled, includes a bottom plate, four columns, four girders, and one or more wall elements. The assembled structure is intended to be disassembled in its entirety. The four girders make up the open ceiling, and the four columns make up the structure for
20 holding the four-girder assembly at a distance above the bottom plate. A significant feature of Bach et al. is that

25

the building must be accessible from above, in other words, the support girders are disposed such that there is unimpeded access to the interior space from above.

5 Architectural models are also present in the prior art. See, for example, U.S. Patent No. 2,315,463 to Tingley et al., U.S. Patent No. 3,295,225 to Sodergren, U.S. Patent No. 3,902,291 to Zucht, and U.S. Patent No. 4,650,437 to Sitkus. Other types of doll houses exist as set forth in U.S. Patent No. 3,526,054 to Raman, U.S. Patent No. 3,996,693 to Walmer, and U.S. Patent No. 6,073,404 to Norfleet.

10 The prior art, however, does not provide a modular house toy having a fixed supporting structure that can be easily combined to create a structure larger than a single fixed supporting structure, and to do so in an easy and inexpensive manner, while simultaneously providing sophisticated household objects/props and electronic lights and sounds.

15 20 What is needed is a modular house toy having a secure foundation that enables easy modularity for constructing a multi-part house and that allows for the addition and inclusion of sophisticated electronics, including, for example, lighting and sound effects.

Summary of the Invention:

It is accordingly an object of the invention to provide a modular house toy that overcomes the hereinafore-mentioned disadvantages of the heretofore-known devices of this general type and that provides an inexpensive and structurally strong modular house toy.

With the foregoing and other objects in view, there is provided, in accordance with the invention, a modular house toy including a fixed supporting structure having a solid floor, a solid ceiling, a solid back wall connecting the floor to the ceiling, and an open arch connecting the floor to the ceiling.

In accordance with another feature of the invention, the back wall and/or the arch permanently connects the floor to the ceiling.

In accordance with a further feature of the invention, the connection of the floor to the ceiling with the back wall is in a first vertical connection plane, and the connection of the floor to the ceiling with the arch is in a second vertical connection plane different from the first vertical connection plane.

In accordance with an added feature of the invention, the floor has floor depressions, the ceiling has ceiling depressions, the back wall has wall extensions, and the arch has arch extensions. At least one of the wall extensions is
5 inserted into at least one of the floor depressions and at least one of the wall extensions is inserted into at least one of the ceiling depressions to connect the floor to the ceiling. Further, at least one of the arch extensions is inserted into at least one of the floor depressions and at
10 least one of the arch extensions is inserted into at least one of the ceiling depressions to connect the floor to the ceiling.

In accordance with an additional feature of the invention, the floor has a top side with two pairs of floor depressions. The ceiling has a bottom side with two pairs of ceiling
15 depressions. The back wall has two lower wall extensions inserted into a first of the two pairs of floor depressions and two upper wall extensions inserted into a first of the two
20 pairs of ceiling depressions to connect the floor to the ceiling. The arch has two lower arch extensions inserted into a second of the two pairs of floor depressions and two upper arch extensions inserted into a second of the two pairs of
25 ceiling depressions to connect the floor to the ceiling.

In accordance with yet another feature of the invention, the floor and the ceiling have the same shape and the back wall and the arch have the same shape to allow repetitious and modular interlocking of one modular house toy to another module house toy.

With the objects of the invention in view, there is also provided a modular house toy configuration including at least two of the fixed supporting structures where the first fixed supporting structure is removably connected to the second fixed supporting structure.

In accordance with a concomitant feature of the invention, the floors and the ceilings of the multiple structures have the same shape and the back walls and the arches of the multiple structures have the same shape to allow repetitious and modular interlocking of one modular house toy to another module house toy.

Other features that are considered as characteristic for the invention are set forth in the appended claims.

Although the invention is illustrated and described herein as embodied in a modular house toy, it is, nevertheless, not intended to be limited to the details shown because various modifications and structural changes may be made therein

without departing from the spirit of the invention and within the scope and range of equivalents of the claims.

The construction and method of operation of the invention, however, together with additional objects and advantages thereof, will be best understood from the following description of specific embodiments when read in connection with the accompanying drawings.

Brief Description of the Drawing:

FIG. 1 is an exploded, perspective view of a disassembled fixed supporting structure of a modular house toy according to the invention;

FIG. 2 is an exploded, perspective view of an assembled fixed supporting structure of FIG. 1 with a roof structure;

FIG. 3 is a side elevational view of three connected fixed supporting structures of FIG. 1;

FIG. 4 is a fragmentary, enlarged, perspective view of a side wall connection of the fixed supporting structure of FIG. 1;

FIG. 5 is a fragmentary, perspective view of a bathroom embodiment of the assembled fixed supporting structure of FIG. 1 with the front arch and one side wall removed;

FIG. 6 is a fragmentary, perspective view of a kitchen embodiment of the assembled fixed supporting structure of FIG. 1 with the front arch and one side wall removed;

5

FIG. 7 is a fragmentary, perspective view of a living room embodiment of the assembled fixed supporting structure of FIG. 1 with the front arch and one side wall removed;

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100

FIG. 8 is a fragmentary, perspective view of a nursery embodiment of the assembled fixed supporting structure of FIG. 1 with the front arch and one side wall removed;

FIG. 9 is a fragmentary, perspective view of a dining room embodiment of the assembled fixed supporting structure of FIG. 1 with the front arch and one side wall removed;

FIG. 10 is a fragmentary, perspective view of a master bedroom embodiment of the assembled fixed supporting structure of FIG. 1 with the front arch and one side wall removed;

Description of the Preferred Embodiments:

In all the figures of the drawing, sub-features and integral parts that correspond to one another bear the same reference symbol in each case.

Referring now to the figures of the drawings in detail and first, particularly to FIG. 1 thereof, there is shown an exploded view of a modular house toy having a fixed supporting structure 1. The fixed supporting structure 1, as shown in
5 FIG. 1 includes a solid floor 2, a solid ceiling 3, a solid back wall 4, and an open front arch 5, which, when assembled (see FIG. 2), together define an inner space 6.

“Fixed,” with respect to the fixed supporting structure 1, is to be understood as meaning that a user will not remove any of the solid floor 2, the solid ceiling 3, the solid back wall 4, or the open front arch 5 after assembly and during normal use of the modular house toy. “Assembly” is to be understood as meaning either assembly of the modular house toy at the manufacturing location or by a toy user immediately after opening the toy from its packaging and before normal use by the user.

“Solid,” with respect to the solid floor 2, is to be understood as meaning that objects do not pass to the inner space 6 through the plane defined by the edges of the solid floor 2 from below the solid floor 2 without breaking the solid floor 2 itself. In other words, when the assembled modular house toy is set down on a solid surface larger than a footprint of the solid floor 2, all access by the user to the
25 space below the solid floor 2 is impeded by the solid floor 2.

0004191 061001
T00T99" T6T+0000

Similarly, "solid," with respect to the solid ceiling 3, is to be understood as meaning that objects do not pass through the plane defined by the edges of the solid ceiling 3, whether
5 from above the solid ceiling 3 to below the solid ceiling 3, or from below the solid ceiling 3 to above the solid ceiling 3 without breaking the solid ceiling 3 itself. In other words, all access by the user to the inside space 6 of an assembled modular house toy through the plane defined by the edges of the solid ceiling 3 is impeded.

Likewise, "solid," with respect to the solid back wall 4, is to be understood as meaning that objects are not intended to pass to the inner space 6 through the plane defined by the edges of the solid back wall 4 from outside the solid back wall 4 without breaking the solid back wall 4 itself. In
other words, all access by the user to the inside space 6 of an assembled modular house toy through the plane defined by the edges of the solid back wall 4 is impeded. There is an
20 exception, however. The solid back wall 4 can have a window 45, as illustrated in FIG. 1. The window 45 is solid and objects cannot pass through the window 45 without breaking the window 45 itself or the solid back wall 4. In an alternative embodiment, however, the window 45 or the panes 46 in the
25 window 45 can be shuttered, either vertically or horizontally, similar to conventional household windows. In a shuttered

embodiment, passage is possible, but only through the rectangular space defined by the window frame 47.

The solid floor 2 has a rectangular footprint. In a preferred embodiment, the footprint is square. The solid floor 2 has a depression 21 in each of the four top side corners. The solid floor 2 also has four side walls 22 that, in a preferred embodiment, are made as one piece with the top side of the solid floor 2. Particularly, the solid floor 2 is made in one piece in an injection molding process. In the preferred embodiment, portions of the side walls 22 make up two of the five walls defining the open box-shaped depression 21 in the floor. Each of the side walls 22 has a cavity 23 and a projection 24. Each cavity 23 preferably has an approximately rectangular shape, and each projection 24 also preferably has an approximately rectangular shape corresponding to each cavity 23. Thus, the cavities 23 and projections 24 are standardized with respect to one another. The projection 24 and cavity 23 can take any shape, however. Further, the cavity 23 and the projection 24 are preferably bow-shaped, as shown in FIG. 1.

Each of the cavities 23 has a recess 29 for receiving a fastener 25. The fastener 25 is, preferably, a circular magnet and the recess 29 has a circular shape corresponding to the magnet. Each of the projections 24 has a recess 29 for

receiving a second fastener 26. Preferably, the fastener 26 is a circular ferrum and the recess 29 has a circular shape corresponding to the ferrum. Preferably, the cavities 23 and projections 24 are staggered around the side walls 22 of the solid floor 2. Thus, when two floors 2 are placed adjacent one another (see FIG. 3), a projection 24 of the first floor 2 mates with a cavity 23 of the second floor 2 and a projection 24 of the second floor 2 mates with a cavity 23 of the first floor 2 to produce a form lock. The projections 24, 34 can be slightly larger than the cavities 23, 33 such that a force lock is produced by a mating of the two. The magnet 25 and ferrum 26 provide an attractive force that holds the two floors 2 together in place.

The solid ceiling 3 has a rectangular footprint. Preferably, the footprint is square and corresponds to the shape of the solid floor 2. The solid ceiling 3 has four side walls 32 that, in a preferred embodiment, are made as one piece with the top side of the solid ceiling 3. The side walls 32 and the top side of the solid ceiling 3, therefore, form an open box. The open box is preferably made in an injection molding process and is used for housing electronic devices for the modular house toy. For example, the open box can house a battery pack, wires, and lights and/or sound devices for a ceiling or wall light, a television, a fireplace, a microwave, a stove, or any other electrically operable item that can be

envisioned to exist in a room of a house. The solid floor 2 additionally or alternatively house such electronics in the cavity formed by the side walls 22 and floor 2.

5 The solid ceiling 3 has a non-illustrated depression in each of the four bottom side corners corresponding to the depression 21 in each of the four top-side corners of the solid floor 2. Preferably, portions of the side walls 32 and portions of the top side of the solid ceiling make up three of the five walls defining the box-shaped depression in the ceiling. Each of the side walls 32 has a cavity 33 and a projection 34. Each cavity 33 has an approximately rectangular shape, and each projection 34 also has an approximately rectangular shape corresponding to each cavity 23, 33. Preferably, the non-illustrated depressions are identical in shape to the depressions 21 in the solid floor 2. Thus, the cavities 23, 33 and projections 24, 34 are standardized with respect to one another. The projection 34 and cavity 33 can take any shape, however. Further, the cavity 33 and the projection 34 are preferably bow-shaped, as shown in FIG. 1.

Also in a preferred embodiment, the cavities 23 and projections 24 on the solid floor 2 are staggered with respect to the cavities 33 and projections 34 on the solid ceiling 3. Each of the cavities 33 has a recess 39 for receiving a

fastener 35. Preferably, the fastener 35 is a circular magnet and the recess 39 has a circular shape corresponding to the magnet. Each of the projections 34 has a recess 39 for receiving a second fastener 36. Preferably, the fastener 36
5 is a circular ferrum and the recess 39 has a circular shape corresponding to the ferrum. Preferably, the cavities 33 and projections 34 are staggered around the side walls 32 of the solid ceiling 3.

10 The open box can be closed by a non-illustrated ceiling plate that is securably fastened to either the side walls 32, the top side of the solid ceiling 3, or both. Thus, a protective enclosure is formed for electronics, or any other device, housed therein.

15 The top side of the solid ceiling 3 has at least one flange 31 projecting transversely to the plane of the top side.

20 Preferably, the top side has two flanges 31 projecting transversely to the plane of the top side near each of the four edges of the top side, for a total of eight flanges 31 as shown. The flanges 31 are used, for example, to secure a roof section 9 (see FIG. 2) from easily falling off or to secure a second modular house toy 1 on top of a first modular house toy 1 as shown in FIG. 3.

The solid back wall 4 has four plugs 41, two side walls 42, and a back wall 43. The two side walls 42 extend at right angles to the back wall 43. Each of the four plugs 41, the two side walls 42, and the back wall 43 are formed integral with one another, preferably in one piece by injection molding. The upper two of the four plugs 41 are configured to be inserted into the corresponding non-illustrated depressions in the lower side of the solid ceiling 3 and the lower two of the four plugs 41 are to be inserted into the two corresponding depressions 21 in the solid floor 2. Preferably, the plugs have a bore 49 with a thread for securably receiving a screw 27, 37 therein.

The open front arch 5 has four plugs 51, two side walls 52, and an upside-down U-shaped front wall 53. Each of the plugs 51, the side walls 52, and the U-shaped front wall 53 are formed integral with one another, preferably by injection molding. The upper two of the four plugs 51 are configured to be inserted into the corresponding non-illustrated depressions in the lower side of the solid ceiling 3 and the lower two of the four plugs 51 are to be inserted into two corresponding depressions 21 in the solid floor 2. Preferably, the plugs have a bore 59 with a thread for securably receiving a screw 27, 37 therein. The open front arch 5 can also have an integral post 54 with a bore therein for receiving another top

screw 37 to provide additionally securing support to the center top part of the open front arch 5.

5 The fixed supporting structure 1 is assembled by inserting the two lowermost plugs 51 of the open front arch 5 into the two front depressions 21 on top of the solid floor 2, and inserting the two lowermost plugs 41 of the solid back wall 4 into the two rear depressions 21 on top of the solid floor 2. At each corner of the solid floor 2, a bottom screw 27 is
10 turned through the bottom of the solid floor 2 and into a respective bottom plug 41, 51 to fixedly and/or permanently secure the plug 41, 51 into its corresponding depression 21. Equivalent fasteners to the screw 27 can also be used. The solid ceiling 3 is placed on top of the open front arch 5 and the solid back wall 4 such that the two uppermost plugs 51 of
15 the open front arch 5 are inserted into the corresponding two non-illustrated front (with respect to the view of FIG. 1) depressions of the bottom side of the solid ceiling 3, and such that the two uppermost plugs 41 of the solid back wall 4
20 are inserted into the corresponding two non-illustrated rear depressions of the bottom side of the solid ceiling 3. At each corner of the solid ceiling 3, a top screw 37 is turned through the top side of the solid ceiling 3 and into a respective top plug 41, 51 to fixedly and/or permanently
25 secure the plug 41, 51 into its corresponding depression. Equivalent fasteners to the screw 37 can also be used.

The modular house toy 1 also includes two removable side walls 7, 8. See FIG. 1. Each of the side walls 7, 8 have at least one connection device, preferably, in the form of at least one tongue. In the preferred configuration, each side wall 7, 8 has at least one tongue 71, 72, 73, 81, 82, 83 on each of the four edges of the respective side wall 7, 8. Particularly, each lateral edge has a centrally disposed lateral tongue 71, 81, each lower edge has a lower edge tongue 72, 82 disposed over almost the entirety of the lower edge, and each upper edge has three upper edge tongues 73, 83 evenly spaced on the upper edge as shown in FIG. 1. The lower edge tongue 82 is preferably more than 80 percent as long as entire lower edge of side wall 8, and, particularly, more than 90 percent as long. The lower edge tongue 72 is preferably more than 80 percent as long as the lower edges on either side of the bottom of the door 75, and, particularly, more than 90 percent as long. Each tongue 71, 72, 73, 81, 82, 83 is preferably rectangular, but can take any shape. For example, the center part of the tongue can be longer (in the tongue-extending direction) than the side portions thereof.

The side walls 42 of the solid back wall 4 and the side walls 52 of the open front arch each have a corresponding groove 48, 58 (see FIG. 4) for receiving a respective lateral tongue 71, 81. Similarly, the solid floor 2 has two grooves 722, 822 for

receiving a respective lower edge tongue 72, 82. Also, the solid ceiling 3, has non-illustrated grooves corresponding to the shape of the upper edge tongues 73, 83. The side walls 7, 8 can have any number of tongues 71, 72, 73, 81, 82, 83.

5 Preferably, for stability, each side wall 7, 8 has at least two tongues disposed symmetrically on opposing edges of the side wall 7, 8.

The connection of one lateral tongue 71, 81 into a corresponding groove 48, 58 can be seen particularly clearly in FIG. 4. Preferably, the side walls 7, 8 are plastic. Therefore, they are somewhat bendable. Insertion of a side wall 7, 8 is performed by inserting a tongue 71, 72, 73, 81, 82, 83 on one of the edges. Preferably, the tongue 72, 82 is first inserted into the corresponding groove 722, 822. Then, the side wall 7, 8 is slightly bent such that the height and width decreases sufficiently enough to insert the second and subsequent edges. Alternatively, the side wall is simply pressed against the side walls 32, 42, 52 until the tongue 71, 72, 73, 81, 82, 83 snaps into the corresponding groove. A non-illustrated bevel can be added to the tongue for ease of connectivity.

In the preferred embodiment of the side walls 7, 8, one side wall 7 of each module of the modular house toy has a door 75 and another side wall 8 has a window 85. If the solid back

wall 4 has a window 45, then the window 85 preferably matches, in configuration, the window 45 in the solid back wall 4.

Each side wall 7 has a configuration that can be interchanged with the other side wall 8 in a modular fashion.

5 Additionally, the four edges of an opening defined by three sides of the open front arch 5 and the solid floor 2 can be equipped with grooves like grooves 48, 58 such that any of the side walls 7, 8 can be inserted into any one of the three apertures of the fixed supporting structure 1 shown in FIGS. 1 and 2.

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100

The following describes an alternative, non-illustrated embodiment of the side wall connector that eliminates many of the tongues and grooves shown in FIG. 1. In the alternative embodiment, the lateral edges of the side walls 7, 8 do not have tongues. With respect to the upper edge of the side walls 7, 8, the upper edge tongues on the side walls 7, 8 are removed and a number of pins, preferably, two, are placed on a side of the side walls facing the inner space 6 and projecting towards the inner space 6. The lower edge flange 72, 82 remains the same as shown in FIG. 1. Accordingly, the non-illustrated grooves in the bottom side of the solid ceiling 3 are removed and one or more flanges projecting from the bottom side of the side walls 32 facing each side wall 7, 8 is added to the solid ceiling 3, preferably, slightly back (i.e., towards the center of the inner space 6) from the side opening

of structures 1 in any configuration desired by the user. For example, four structures 1 can be disposed in a row to form a four-room single level house. Four structures 1 also can be disposed as a square duplex with two adjacent structures 1 below and two adjacent structures 1 above. Alternatively, four structures can be disposed as a two-level house with three adjacent structures 1 below and one structure 1 above. FIG. 3 depicts a two-level house made of three structures 1 where two lower structures 1A, 1B are placed adjacent one another and one structure 1C is disposed on top of the lower structure 1A.

To attach a first fixed supporting structure 1C on top of a second fixed supporting structure 1A, as shown in FIG. 3, the first structure 1C is placed upon the second structure 1A such that the flanges 31, extending upward from the top side of the solid ceiling 3A of the second structure 1A, are inserted into four non-illustrated grooves on the bottom side of the solid floor 2C of the first structure 1C. The bottom side of a solid floor 2 can have any device or means for securing the solid floor 2 to the lower disposed solid ceiling 3. A groove corresponding to the flanges 31, as set forth above, is preferred. Alternatively, the solid floor 2 can have a grating underneath with groove-like cutouts for accommodating the flanges 31. In another alternative to the flanges 31 for attaching a roof section 9 or a second modular house toy 1 to

FIG. 10
FIG. 11
FIG. 12
FIG. 13
FIG. 14
FIG. 15
FIG. 16
FIG. 17
FIG. 18
FIG. 19
FIG. 20
FIG. 21
FIG. 22
FIG. 23
FIG. 24
FIG. 25
FIG. 26
FIG. 27
FIG. 28
FIG. 29
FIG. 30
FIG. 31
FIG. 32
FIG. 33
FIG. 34
FIG. 35
FIG. 36
FIG. 37
FIG. 38
FIG. 39
FIG. 40
FIG. 41
FIG. 42
FIG. 43
FIG. 44
FIG. 45
FIG. 46
FIG. 47
FIG. 48
FIG. 49
FIG. 50
FIG. 51
FIG. 52
FIG. 53
FIG. 54
FIG. 55
FIG. 56
FIG. 57
FIG. 58
FIG. 59
FIG. 60
FIG. 61
FIG. 62
FIG. 63
FIG. 64
FIG. 65
FIG. 66
FIG. 67
FIG. 68
FIG. 69
FIG. 70
FIG. 71
FIG. 72
FIG. 73
FIG. 74
FIG. 75
FIG. 76
FIG. 77
FIG. 78
FIG. 79
FIG. 80
FIG. 81
FIG. 82
FIG. 83
FIG. 84
FIG. 85
FIG. 86
FIG. 87
FIG. 88
FIG. 89
FIG. 90
FIG. 91
FIG. 92
FIG. 93
FIG. 94
FIG. 95
FIG. 96
FIG. 97
FIG. 98
FIG. 99
FIG. 100
FIG. 101
FIG. 102
FIG. 103
FIG. 104
FIG. 105
FIG. 106
FIG. 107
FIG. 108
FIG. 109
FIG. 110
FIG. 111
FIG. 112
FIG. 113
FIG. 114
FIG. 115
FIG. 116
FIG. 117
FIG. 118
FIG. 119
FIG. 120
FIG. 121
FIG. 122
FIG. 123
FIG. 124
FIG. 125
FIG. 126
FIG. 127
FIG. 128
FIG. 129
FIG. 130
FIG. 131
FIG. 132
FIG. 133
FIG. 134
FIG. 135
FIG. 136
FIG. 137
FIG. 138
FIG. 139
FIG. 140
FIG. 141
FIG. 142
FIG. 143
FIG. 144
FIG. 145
FIG. 146
FIG. 147
FIG. 148
FIG. 149
FIG. 150
FIG. 151
FIG. 152
FIG. 153
FIG. 154
FIG. 155
FIG. 156
FIG. 157
FIG. 158
FIG. 159
FIG. 160
FIG. 161
FIG. 162
FIG. 163
FIG. 164
FIG. 165
FIG. 166
FIG. 167
FIG. 168
FIG. 169
FIG. 170
FIG. 171
FIG. 172
FIG. 173
FIG. 174
FIG. 175
FIG. 176
FIG. 177
FIG. 178
FIG. 179
FIG. 180
FIG. 181
FIG. 182
FIG. 183
FIG. 184
FIG. 185
FIG. 186
FIG. 187
FIG. 188
FIG. 189
FIG. 190
FIG. 191
FIG. 192
FIG. 193
FIG. 194
FIG. 195
FIG. 196
FIG. 197
FIG. 198
FIG. 199
FIG. 200
FIG. 201
FIG. 202
FIG. 203
FIG. 204
FIG. 205
FIG. 206
FIG. 207
FIG. 208
FIG. 209
FIG. 210
FIG. 211
FIG. 212
FIG. 213
FIG. 214
FIG. 215
FIG. 216
FIG. 217
FIG. 218
FIG. 219
FIG. 220
FIG. 221
FIG. 222
FIG. 223
FIG. 224
FIG. 225
FIG. 226
FIG. 227
FIG. 228
FIG. 229
FIG. 230
FIG. 231
FIG. 232
FIG. 233
FIG. 234
FIG. 235
FIG. 236
FIG. 237
FIG. 238
FIG. 239
FIG. 240
FIG. 241
FIG. 242
FIG. 243
FIG. 244
FIG. 245
FIG. 246
FIG. 247
FIG. 248
FIG. 249
FIG. 250
FIG. 251
FIG. 252
FIG. 253
FIG. 254
FIG. 255
FIG. 256
FIG. 257
FIG. 258
FIG. 259
FIG. 260
FIG. 261
FIG. 262
FIG. 263
FIG. 264
FIG. 265
FIG. 266
FIG. 267
FIG. 268
FIG. 269
FIG. 270
FIG. 271
FIG. 272
FIG. 273
FIG. 274
FIG. 275
FIG. 276
FIG. 277
FIG. 278
FIG. 279
FIG. 280
FIG. 281
FIG. 282
FIG. 283
FIG. 284
FIG. 285
FIG. 286
FIG. 287
FIG. 288
FIG. 289
FIG. 290
FIG. 291
FIG. 292
FIG. 293
FIG. 294
FIG. 295
FIG. 296
FIG. 297
FIG. 298
FIG. 299
FIG. 300
FIG. 301
FIG. 302
FIG. 303
FIG. 304
FIG. 305
FIG. 306
FIG. 307
FIG. 308
FIG. 309
FIG. 310
FIG. 311
FIG. 312
FIG. 313
FIG. 314
FIG. 315
FIG. 316
FIG. 317
FIG. 318
FIG. 319
FIG. 320
FIG. 321
FIG. 322
FIG. 323
FIG. 324
FIG. 325
FIG. 326
FIG. 327
FIG. 328
FIG. 329
FIG. 330
FIG. 331
FIG. 332
FIG. 333
FIG. 334
FIG. 335
FIG. 336
FIG. 337
FIG. 338
FIG. 339
FIG. 340
FIG. 341
FIG. 342
FIG. 343
FIG. 344
FIG. 345
FIG. 346
FIG. 347
FIG. 348
FIG. 349
FIG. 350
FIG. 351
FIG. 352
FIG. 353
FIG. 354
FIG. 355
FIG. 356
FIG. 357
FIG. 358
FIG. 359
FIG. 360
FIG. 361
FIG. 362
FIG. 363
FIG. 364
FIG. 365
FIG. 366
FIG. 367
FIG. 368
FIG. 369
FIG. 370
FIG. 371
FIG. 372
FIG. 373
FIG. 374
FIG. 375
FIG. 376
FIG. 377
FIG. 378
FIG. 379
FIG. 380
FIG. 381
FIG. 382
FIG. 383
FIG. 384
FIG. 385
FIG. 386
FIG. 387
FIG. 388
FIG. 389
FIG. 390
FIG. 391
FIG. 392
FIG. 393
FIG. 394
FIG. 395
FIG. 396
FIG. 397
FIG. 398
FIG. 399
FIG. 400
FIG. 401
FIG. 402
FIG. 403
FIG. 404
FIG. 405
FIG. 406
FIG. 407
FIG. 408
FIG. 409
FIG. 410
FIG. 411
FIG. 412
FIG. 413
FIG. 414
FIG. 415
FIG. 416
FIG. 417
FIG. 418
FIG. 419
FIG. 420
FIG. 421
FIG. 422
FIG. 423
FIG. 424
FIG. 425
FIG. 426
FIG. 427
FIG. 428
FIG. 429
FIG. 430
FIG. 431
FIG. 432
FIG. 433
FIG. 434
FIG. 435
FIG. 436
FIG. 437
FIG. 438
FIG. 439
FIG. 440
FIG. 441
FIG. 442
FIG. 443
FIG. 444
FIG. 445
FIG. 446
FIG. 447
FIG. 448
FIG. 449
FIG. 450
FIG. 451
FIG. 452
FIG. 453
FIG. 454
FIG. 455
FIG. 456
FIG. 457
FIG. 458
FIG. 459
FIG. 460
FIG. 461
FIG. 462
FIG. 463
FIG. 464
FIG. 465
FIG. 466
FIG. 467
FIG. 468
FIG. 469
FIG. 470
FIG. 471
FIG. 472
FIG. 473
FIG. 474
FIG. 475
FIG. 476
FIG. 477
FIG. 478
FIG. 479
FIG. 480
FIG. 481
FIG. 482
FIG. 483
FIG. 484
FIG. 485
FIG. 486
FIG. 487
FIG. 488
FIG. 489
FIG. 490
FIG. 491
FIG. 492
FIG. 493
FIG. 494
FIG. 495
FIG. 496
FIG. 497
FIG. 498
FIG. 499
FIG. 500
FIG. 501
FIG. 502
FIG. 503
FIG. 504
FIG. 505
FIG. 506
FIG. 507
FIG. 508
FIG. 509
FIG. 510
FIG. 511
FIG. 512
FIG. 513
FIG. 514
FIG. 515
FIG. 516
FIG. 517
FIG. 518
FIG. 519
FIG. 520
FIG. 521
FIG. 522
FIG. 523
FIG. 524
FIG. 525
FIG. 526
FIG. 527
FIG. 528
FIG. 529
FIG. 530
FIG. 531
FIG. 532
FIG. 533
FIG. 534
FIG. 535
FIG. 536
FIG. 537
FIG. 538
FIG. 539
FIG. 540
FIG. 541
FIG. 542
FIG. 543
FIG. 544
FIG. 545
FIG. 546
FIG. 547
FIG. 548
FIG. 549
FIG. 550
FIG. 551
FIG. 552
FIG. 553
FIG. 554
FIG. 555
FIG. 556
FIG. 557
FIG. 558
FIG. 559
FIG. 560
FIG. 561
FIG. 562
FIG. 563
FIG. 564
FIG. 565
FIG. 566
FIG. 567
FIG. 568
FIG. 569
FIG. 570
FIG. 571
FIG. 572
FIG. 573
FIG. 574
FIG. 575
FIG. 576
FIG. 577
FIG. 578
FIG. 579
FIG. 580
FIG. 581
FIG. 582
FIG. 583
FIG. 584
FIG. 585
FIG. 586
FIG. 587
FIG. 588
FIG. 589
FIG. 590
FIG. 591
FIG. 592
FIG. 593
FIG. 594
FIG. 595
FIG. 596
FIG. 597
FIG. 598
FIG. 599
FIG. 600
FIG. 601
FIG. 602
FIG. 603
FIG. 604
FIG. 605
FIG. 606
FIG. 607
FIG. 608
FIG. 609
FIG. 610
FIG. 611
FIG. 612
FIG. 613
FIG. 614
FIG. 615
FIG. 616
FIG. 617
FIG. 618
FIG. 619
FIG. 620
FIG. 621
FIG. 622
FIG. 623
FIG. 624
FIG. 625
FIG. 626
FIG. 627
FIG. 628
FIG. 629
FIG. 630
FIG. 631
FIG. 632
FIG. 633
FIG. 634
FIG. 635
FIG. 636
FIG. 637
FIG. 638
FIG. 639
FIG. 640
FIG. 641
FIG. 642
FIG. 643
FIG. 644
FIG. 645
FIG. 646
FIG. 647
FIG. 648
FIG. 649
FIG. 650
FIG. 651
FIG. 652
FIG. 653
FIG. 654
FIG. 655
FIG. 656
FIG. 657
FIG. 658
FIG. 659
FIG. 660
FIG. 661
FIG. 662
FIG. 663
FIG. 664
FIG. 665
FIG. 666
FIG. 667
FIG. 668
FIG. 669
FIG. 670
FIG. 671
FIG. 672
FIG. 673
FIG. 674
FIG. 675
FIG. 676
FIG. 677
FIG. 678
FIG. 679
FIG. 680
FIG. 681
FIG. 682
FIG. 683
FIG. 684
FIG. 685
FIG. 686
FIG. 687
FIG. 688
FIG. 689
FIG. 690
FIG. 691
FIG. 692
FIG. 693
FIG. 694
FIG. 695
FIG. 696
FIG. 697
FIG. 698
FIG. 699
FIG. 700
FIG. 701
FIG. 702
FIG. 703
FIG. 704
FIG. 705
FIG. 706
FIG. 707
FIG. 708
FIG. 709
FIG. 710
FIG. 711
FIG. 712
FIG. 713
FIG. 714
FIG. 715
FIG. 716
FIG. 717
FIG. 718
FIG. 719
FIG. 720
FIG. 721
FIG. 722
FIG. 723
FIG. 724
FIG. 725
FIG. 726
FIG. 727
FIG. 728
FIG. 729
FIG. 730
FIG. 731
FIG. 732
FIG. 733
FIG. 734
FIG. 735
FIG. 736
FIG. 737
FIG. 738
FIG. 739
FIG. 740
FIG. 741
FIG. 742
FIG. 743
FIG. 744
FIG. 745
FIG. 746
FIG. 747
FIG. 748
FIG. 749
FIG. 750
FIG. 751
FIG. 752
FIG. 753
FIG. 754
FIG. 755
FIG. 756
FIG. 757
FIG. 758
FIG. 759
FIG. 760
FIG. 761
FIG. 762
FIG. 763
FIG. 764
FIG. 765
FIG. 766
FIG. 767
FIG. 768
FIG. 769
FIG. 770
FIG. 771
FIG. 772
FIG. 773
FIG. 774
FIG. 775
FIG. 776
FIG. 777
FIG. 778
FIG. 779
FIG. 780
FIG. 781
FIG. 782
FIG. 783
FIG. 784
FIG. 785
FIG. 786
FIG. 787
FIG. 788
FIG. 789
FIG. 790
FIG. 791
FIG. 792
FIG. 793
FIG. 794
FIG. 795
FIG. 796
FIG. 797
FIG. 798
FIG. 799
FIG. 800
FIG. 801
FIG. 802
FIG. 803
FIG. 804
FIG. 805
FIG. 806
FIG. 807
FIG. 808
FIG. 809
FIG. 810
FIG. 811
FIG. 812
FIG. 813
FIG. 814
FIG. 815
FIG. 816
FIG. 817
FIG. 818
FIG. 819
FIG. 820
FIG. 821
FIG. 822
FIG. 823
FIG. 824
FIG. 825
FIG. 826
FIG. 827
FIG. 828
FIG. 829
FIG. 830
FIG. 831
FIG. 832
FIG. 833
FIG. 834
FIG. 835
FIG. 836
FIG. 837
FIG. 838
FIG. 839
FIG. 840
FIG. 841
FIG. 842
FIG. 843
FIG. 844
FIG. 845
FIG. 846
FIG. 847
FIG. 848
FIG. 849
FIG. 850
FIG. 851
FIG. 852
FIG. 853
FIG. 854
FIG. 855
FIG. 856
FIG. 857
FIG. 858
FIG. 859
FIG. 860
FIG. 861
FIG. 862
FIG. 863
FIG. 864
FIG. 865
FIG. 866
FIG. 867
FIG. 868
FIG. 869
FIG. 870
FIG. 871
FIG. 872
FIG. 873
FIG. 874
FIG. 875
FIG. 876
FIG. 877
FIG. 878
FIG. 879
FIG. 880
FIG. 881
FIG. 882
FIG. 883
FIG. 884
FIG. 885
FIG. 886
FIG. 887
FIG. 888
FIG. 889
FIG. 890
FIG. 891
FIG. 892
FIG. 893
FIG. 894
FIG. 895
FIG. 896
FIG. 897
FIG. 898
FIG. 899
FIG. 900
FIG. 901
FIG. 902
FIG. 903
FIG. 904
FIG. 905
FIG. 906
FIG. 907
FIG. 908
FIG. 909
FIG. 910
FIG. 911
FIG. 912
FIG. 913
FIG. 914
FIG. 915
FIG. 916
FIG. 917
FIG. 918
FIG. 919
FIG. 920
FIG. 921
FIG. 922
FIG. 923
FIG. 924
FIG. 925
FIG. 926
FIG. 927
FIG. 928
FIG. 929
FIG. 930
FIG. 931
FIG. 932
FIG. 933
FIG. 934
FIG. 935
FIG. 936
FIG. 937
FIG. 938
FIG. 939
FIG. 940
FIG. 941
FIG. 942
FIG. 943
FIG. 944
FIG. 945
FIG. 946
FIG. 947
FIG. 948
FIG. 949
FIG. 950
FIG. 951
FIG. 952
FIG. 953
FIG. 954
FIG. 955
FIG. 956
FIG. 957
FIG. 958
FIG. 959
FIG. 960
FIG. 961
FIG. 962
FIG. 963
FIG. 964
FIG. 965
FIG. 966
FIG. 967
FIG. 968
FIG. 969
FIG. 970
FIG. 971
FIG. 972
FIG. 973
FIG. 974
FIG. 975
FIG. 976
FIG. 977
FIG. 978
FIG. 979
FIG. 980
FIG. 981
FIG. 982
FIG. 983
FIG. 984
FIG. 985
FIG. 986
FIG. 987
FIG. 988
FIG. 989
FIG. 990
FIG. 991
FIG. 992
FIG. 993
FIG. 994
FIG. 995
FIG. 996
FIG. 997
FIG. 998
FIG. 999
FIG. 1000

a first modular house toy 1, the solid ceiling 3 can have vertically-extending plugs corresponding to the upper plugs 51 of the open front arch 5 and the upper plugs 41 of the solid back wall 4. In the alternative embodiment, the solid floor 2 has four depressions on the non-illustrated underside (corresponding to the depressions 21 shown on the upper side of the solid floor 2) for receiving the vertically-extending plugs. Such plugs provide substantial support for a roof section 9 or a second story structure 1. Other alternative equivalent connection embodiments are also possible so long as the roof structure 9 or other supporting structure 1 remain easily secured to and easily removed from the other supporting structure 1. Additionally, a ceiling 3 can have magnets 25 and a floor 2 can have ferrums 26 (or vice-versa) for additional releasably-connective support of two supporting structures 1A, 1C.

Each of the features and alternatives for connecting one structure 1C on top of another structure can be reproduced for the bottom side of the roof structure 9. While the roof structure 9 is depicted as a conventional gabled roof, the roof structure can take any shape. For example, the roof can be in the form of a sun deck.

To attach a third fixed supporting structure 1B immediately adjacent to the second fixed supporting structure 1A, the

third structure 1B is placed next to the second structure 1A such that, preferably, two projections 24, 34 on a left side of the third structure 1B (one upper and one lower) are inserted into two cavities 23, 33 on a right side of the second structure 1A (one upper and one lower) and two projections 24, 34 on the right side of the second structure 1A (one upper and one lower) are inserted into two cavities 23, 33 on the left side of the third structure 1B (one upper and one lower). The cavities 23, 33 and the projections 24, 34 are shaped preferably to provide both a form lock and a force lock to keep the two adjacent fixed supporting structures 1A, 1B together as set forth above. The magnets 25, 35 inside the cavities 23, 33 and the ferrums 26, 36 inside the projections 24, 34 are mutually attracted to provide an additional holding force that keeps the two fixed supporting structures 1A, 1B together.

Either the user or the manufacturer can assemble the fixed supporting structure 1, including the solid floor 2, the solid ceiling 3, the solid back wall 4, and the open front arch 5. Preferably, the magnets 25, 35 are fixedly and/or permanently secured into corresponding recesses 29 and the ferrums 26, 36 are fixedly and/or permanently secured into other corresponding recesses 29 by the manufacturer. Alternatively, the magnets 25, 35 and ferrums 26, 36 can be installed by the user.

FIG. 5 shows a preferred embodiment of fixed supporting structure 1 as a bathroom. The bathroom is shown with a solid floor 2, a solid ceiling 3, a solid back wall 4, a side wall 8 with a window 85, and a roof structure 9. The side wall 7 and the open front arch 5 are not shown for the sake of clarity. The bathroom is shown with a bathtub 501, a toilet 502, a sink cabinet 503, and a medicine cabinet/vanity 504, for example.

FIG. 6 shows a preferred embodiment of fixed supporting structure 1 as a kitchen. The kitchen is shown with a solid floor 2, a solid ceiling 3, a solid back wall 4, a side wall 8 with a window 85, and a roof structure 9. The side wall 7 and the open front arch 5 are not shown for the sake of clarity. The kitchen is shown with a refrigerator 601, sink cabinet 602, stove 603, counter 604, microwave 605, and cabinetry 606, for example.

FIG. 7 shows a preferred embodiment of fixed supporting structure 1 as a living room. The living room is shown with a solid floor 2, a solid ceiling 3, a solid back wall 4, a side wall 8 with a window 85, and a roof structure 9. The side wall 7 and the open front arch 5 are not shown for the sake of clarity. The living room is shown with a fireplace 701 and an entertainment center 702, for example.

FIG. 8 shows a preferred embodiment of fixed supporting structure 1 as a nursery. The nursery is shown with a solid floor 2, a solid ceiling 3, a solid back wall 4, a side wall 8 with a window 85, and a roof structure 9. The side wall 7 and the open front arch 5 are not shown for the sake of clarity. The nursery is shown with a crib 801 and a teddy bear light switch 802, for example.

FIG. 9 shows a preferred embodiment of fixed supporting structure 1 as a dining room. The dining room is shown with a solid floor 2, a solid ceiling 3, a solid back wall 4, a side wall 7 with a door 75, and a roof structure 9. The side wall 8 and the open front arch 5 are not shown for the sake of clarity. The dining room is shown with two dining hutches 901, for example.

FIG. 10 shows a preferred embodiment of fixed supporting structure 1 as a master bedroom. The master bedroom is shown with a solid floor 2, a solid ceiling 3, a solid back wall 4, a side wall 8, and a roof structure 9. The side wall 7 and the open front arch 5 are not shown for the sake of clarity. The master bedroom is shown with an end table with radio 1001, an end table with telephone 1002, and a bed 1003, for example.

Other alternative examples of the fixed supporting structure include, for example, a bedroom, a garage, an entertainment room, a gym or workout room, a foyer, and a sun room.